

IrriPipe

Blank Irrigation Pipes

Metzer blank irrigation pipes (without integral drippers) provide efficient and adaptable water distribution for precision irrigation, drip systems, micro-sprinklers, landscaping, and mining applications. Supplied coiled in 12–40 mm diameters, these pipes are built to meet diverse field needs. Designed for flexibility and consistent performance, they support efficient water delivery in various setups. Our pipes are available with a coloured layer of various colours: white, brown and purple.



Features & Benefits

- **Versatile Application:**
Ideal for drip systems, micro-sprinklers, mining, and landscaping water distribution.
- **Simple Handling:**
Supplied coiled in manageable sizes for fast and hassle-free field layout and expansion.
- **Design Flexibility:**
Easily tailored for different irrigation setups and crop patterns, supports on-demand positioning.
- **Consistent Water Delivery:**
Smooth interior and reliable construction promote even water flow, reducing system blockages and performance issue
- **Adaptability for advanced applications**
proprietary technological solutions such as Cleanline® and WasteFlow® can be applied in the pipes internal layer

Specifications

- IrriPipes diameter range: 16-40 mm
- Laser marked for QA & supply chain management purposes
- 100% recyclable
- Production & quality management according to ISO9621 standard
- All pipes models are available in 25m,50m,100m,200m,300m,400m coils
- Packed to be delivered in standard sea freight containers.
- Pipes are available with a coloured layer of various colours: white, brown and purple
- Pipes are available with a Cleanline or WasteFlow internal layer

IrriPipe

IrriPipes Technical Data LDPE quality class

Model	Pipe O.D. (mm)	Max working pressure (Bar)	Wall Thickness (mm)	Material class	Coils length (m)
12/5	12	5	1.1	PE32	25/50/100/200/400
16/4	16	4	1.2	PE32	25,50,100
20/2.5	20	2.5	1.0	PE32	25,50,100
20/4	20	4	1.5	PE32	25,50,100
20/6	20	6	2.3	PE32	25,50,100
25/4	25	4	1.9	PE32	25,50,100
25/6	25	6	2.8	PE32	25,50,100
32/4	32	4	2.4	PE32	25,50,100
40/4	40	4	3	PE32	25/50/100

HDPE quality class

Model	Pipe O.D. (mm)	Max working pressure (Bar)	Wall Thickness (mm)	Material class	Packing type Coils (m) /Rod (m)
16/10	16	10	1.5	PE63	25,50,100
20/10	20	10	1.9	PE63	25,50,100
25/6	25	6	1.5	PE63	25,50,100
32/6	32	6	1.9	PE63	25,50,100
32/4	32	4	1.3	PE63	25,50,100
40/4	40	4	1.6	PE63	25,50,100

Calculate IrriPipe performance with our
Irrimetzer app!



Keep in touch!



info@metzerplas.com



metzer-group.com



Notwithstanding anything to the contrary, (A) any information, data, figures, descriptions or any other content included in, or referred to, this document (collectively - "Information") are provided merely (i) on an "as is", "as available" basis only, without any kind of representation, warranty, liability, responsibility and/or undertaking on the part of Metzerplas and/or anyone acting on its behalf, and (ii) for general, informational purposes only, and (B) the Information or any content contained in this document do not constitute, in any way, any professional advice, recommendation or guidance and/or any sort of consultancy and must not be relied on as such. In making a decision, the recipient or reader of the Information must rely solely on its own calculations and examination of the Information, including the merits and risks involved.